

Operating Instructions P0250 Mini Hygro-Thermometer

Congratulations on your purchase of the P0250 Mini Hygro-Thermometer. You have acquired a precision electronic instrument for measuring the temperature, humidity and the current highest and lowest values of both. It is ideal for use inside a wine cellar, car, greenhouse, humidor or refrigerator. This unit will provide you with years of service if cared for properly. Please read these operating instructions thoroughly before use.

Use:

- Open the battery compartment by pushing the cover on the back of the instrument downwards as indicated by the arrow. Remove the battery safety strip, replace battery (positive (+) side up) and remove the protection sheet on the display. The instrument is now ready for use.
- The display now shows the current temperature in °F and the relative humidity in %.
- Displaying maximum/minimum values:
 - a. When you press the MAX/MIN button, the highest values since the unit was last reset appear. This display will inform you of the highest temperature and humidity the unit has measured since the last reset.
 - b. Pressing the same button again displays the lowest values since the unit was last reset.
 - c. To return to current values, press the MAX/MIN button again.
- Resetting the MAX/MIN memory to the present values:
 - a. Press the CLEAR button for 1 second when in MAX or MIN mode.
 - b. Note that pressing the CLEAR button while in normal mode will have no effect.
- The unit can be hung using the enclosed foam tape, magnetic strips, or set on a table or desk using the fold out stand.
- When the display dims or the reading is erratic, replace the battery with an LR44 or AG13 type button cell (positive (+) side up). Please dispose of exhausted batteries properly.

Specifications:

Limits: Temperature: 14 °F - 140 °F
Humidity: 10% to 99% R.H.

Maximum Error: +/- 1.8 °F within 14 °F to 122 °F
+/- 2 °F otherwise
+/- 5% R.H. within 25% to 95% R.H. and 32 °F to 122 °F
+/- 6% R.H. otherwise

Battery: LR44/AG13 Button Cell

Applications:

Humidor

A cigar is to be savored. The subtle flavor of each cigar is a signature of the region from which it hails. The best method of preserving this intended flavor is the humidor, but your humidor might not be doing the job it should be. Over humidifying can lead to improper burning and mildew, while under humidifying will rob your cigars of their true flavor, making them taste harsh. Digital temperature and humidity display shows the precise condition of your cigar's home. The Max/Min humidity and temperature display allows you to finally pin down the exact day you need to refill your humidor's water supply.

Common wisdom holds that humidors perform best when the humidity is maintained at approximately 70%. Place the Mini Hygro-Thermometer inside your Humidor using the enclosed foam tape or magnetic strips. Or you can use the fold out stand.

Refrigerator

Recent news reports have illustrated the dangers of improperly storing food. Illness and injury can result. Use the Mini Hygro-Thermometer inside your refrigerator to monitor the maximum temperature your food experiences. Since refrigerator compressors cycle on and off, the interior temperature of your refrigerator can vary significantly. Most units feature temperature controls but do not inform you of the achieved temperature.

The Max/Min humidity and temperature display allows you to finally find out just what effect those controls have. Common wisdom holds that the temperature in refrigerator should not rise above 40 °F for an extended period. Reset the Max/Min display, then allow your refrigerator to cycle on and off. After a few hours or days you can check the Max display to determine how well your refrigerator is functioning.

! Be aware that holding the refrigerator door open for extended periods will allow the air temperature inside to rise and may give misleading readings.

! Do not affix the Mini Hygro-Thermometer to the inner walls or inner door of the refrigerator. The surface of these walls is warmer than the interior of your refrigerator. Placement on these walls will lead to misleading readings. Use the fold out stand to place the unit in the central area of your refrigerator.

Wine Cellar

When stored properly, wine can improve in quality over time. Proper storage conditions are critical to this aging process. Use the Mini Hygro-Thermometer in your wine storage area to monitor these conditions. The Max/Min display will allow you to check up on ever changing temperature and humidity conditions. Common wisdom holds that temperatures between 52 and 55 °F and humidity between 50 % and 80 % are best for wine. Bottles should be stored on their side to keep the bottom of their corks moist. Humidity keeps the top of the corks moist. Dry corks allow a poor seal causing evaporation and air exposure.

Attach the Mini Hygro-Thermometer to your Wine Cellar wall using the enclosed foam tape or magnetic strips. Or you can use the fold out stand.

! If you have a refrigerator-style Wine Cellar do not affix the Mini Hygro-Thermometer to the inner walls or inner door of the refrigerator. The surface of these walls is warmer than the interior of your refrigerator. Placement on these walls will lead to misleading readings. Use the fold out stand to place the unit in the central area of your refrigerator.

P3 INTERNATIONAL CORPORATION LIMITED WARRANTY

P3 INTERNATIONAL CORPORATION ("P3") warrants to the original retail purchaser only, that its product is free from defects in material or workmanship under the condition of normal use and service for a period of six (6) months from the date of purchase. In the event that a defect, malfunction or failure occurs or is discovered during the warranty period, P3 will repair or replace at its option the product or component part(s) which shall appear in the reasonable judgment of P3 to be defective or not to factory specifications. A product requiring service is to be returned to P3 along with the sales receipt or other proof of purchase acceptable to P3 and a statement describing the defect or malfunction. All transportation costs shall be borne by the owner and the risk of loss shall be upon the party initiating the transportation. All items repaired or replaced thereunder shall be subjected to the same limited warranty for a period of six (6) months from the day P3 ships the repaired or replaced product. The warranty does not apply to any product that has been subject to misuse, tampering, neglect, or accident or as a result of unauthorized alterations or repairs to the product. This warranty is void if the serial number (if any) has been removed, altered, or defaced. This warranty is in lieu of all warranties expressed or implied, including the implied warranties of merchantability and fitness for a particular purpose which are expressly excluded or disclaimed. P3 shall not be responsible for consequential, incidental or other damages, and P3 expressly excludes and disclaims liability for any damages resulting from the use, operation, improper application, malfunction or defeat of any P3 product covered by this limited warranty. P3's obligation is strictly and exclusively limited to the replacement or repair of any defective product or component part(s). Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. P3 does not assume or authorize anyone to assume for it any other obligation whatsoever. Some states do not allow limitation on how long an implied warranty lasts, so the above limitations may not apply to you. It is the owner/user's responsibility to comply with local, state, or federal regulations, if any, that may pertain to P3 products or their use. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

If you experience difficulty in the operation of your unit, or if your unit requires repair please contact:

P3 INTERNATIONAL CORPORATION
TECHNICAL SUPPORT
71 West 23rd Street
Suite 1201
New York, NY 10010-4102

Tel: 212-741-7289

Fax: 212-741-2288

Email: techsupport@p3international.com